


Description

Passivated high commutation triacs in a plastic envelope intended for use in circuits where high static and dynamic dV/dt and high dI/dt can occur. These devices will commute the full rated ms current at the maximum rated junction temperature without the aid of a snubber.


Simplified outline TO-220AB



Features

- Blocking voltage to 600 V
- On-state RMS current to 12 A

Symbol



Applications

- Motor control
- Industrial and domestic lighting
- Heating
- Static switching

Pin	Description
1	Main terminal 1 (T1)
2	Main terminal 2 (T2)
3	gate (G)
TAB	isolated

SYMBOL	PARAMETER	Value	Unit
V_{DRM}	Repetitive peak off-state voltages	600	V
$I_{T(RMS)}$	RMS on-state current (full sine wave)	12	A
I_{TSM}	Non-repetitive peak on-state current (full cycle, T_j initial=25°C)	126	A

SYMBOL	PARAMETER	CONDITIONS	MIN	TYP	MAX	UNIT
$R_{th(j-c)}$	Junction to case(AC)		-	2.3	-	°C/W
$R_{th(j-a)}$	Junction to ambient		-	60	-	°C/W

SYMBOL	PARAMETER	CONDITIONS		MIN	Value	UNIT
V_{DSM}/V_{RSM}	Non repetitive surge peak off-state voltage	tp=10ms	$T_j=25^\circ\text{C}$	-	$V_{DRM}/V_{RRM} + 100$	V
$I_{T(RMS)}$	RMS on-state current	full sine wave; $T_c=90^\circ\text{C}$		-	12	A
I_{TSM}	Non repetitive surge peak on-state current	full cycle, T_j initial= 25°C	F=50Hz t=20ms	-	120	A
			F=60Hz t=16.7ms	-	126	A
I^2t	I^2t Value for fusing	tp=10ms		-	78	A ² S
di/dt	Critical rate of rise of on-state current	$I_G=2x I_{GT}$, tr<=100ns	F=120Hz $T_j=125^\circ\text{C}$	-	50	A/ μ s
I_{GM}	Peak gate current		tp=20us $T_j=125^\circ\text{C}$	-	4	A
I_{DRM}	$V_{DRM}=V_{RRM}$		$T_j=25^\circ\text{C}$	-	5	μ A
I_{RRM}	$V_{DRM}=V_{RRM}$		$T_j=125^\circ\text{C}$	-	1	mA
$P_{G(AV)}$	Average gate power dissipation		$T_j=125^\circ\text{C}$	-	1	W
T_{stg}	Storage junction temperature range			-40	150	$^\circ\text{C}$
T_j	Operating junction Temperature range			-40	125	$^\circ\text{C}$

$T_j=25^\circ\text{C}$ unless otherwise stated

SYMBOL	PARAMETER	CONDITIONS	MIN	TYP	MAX	UNIT
Static characteristics						
$I_{GT}(1)$ V_{GT}		$V_D=12\text{V}$; $R_L=30\ \Omega$ I-II-III I-II-III	-	-	35 1.3	mA V
I_L		$I_G=1.2 I_{GT}$ I-III II	- -	- -	50 60	mA
$I_H(2)$		$I_T=100\text{mA}$	-	-	35	mA
V_{GD}		$V_D=V_{DRM}$ $R_L=3.3\text{K}\ \Omega$ $T_j=125^\circ\text{C}$ I-II-III	0.2	-	-	V
dV/dt(2)		$V_D=67\%V_{DRM}$ gate open; $T_j=125^\circ\text{C}$	500	-	-	V/ μ s
(di/dt)c(2)		without snubber $T_j=125^\circ\text{C}$	6.5	-	-	A/ms

Dynamic Characteristics

$V_T(2)$	$I_{TM}=17\text{A}$ tp=380 μ s	$T_j=25^\circ\text{C}$	-	-	1.55	V
$V_{to}(2)$ $R_d(2)$	Threshold voltage Dynamic resistance	$T_j=125^\circ\text{C}$ $T_j=125^\circ\text{C}$	-	-	0.85 35	V m Ω

Note 1: minimum I_{GT} is guaranteed at 5% of I_{GT} max.

Note 2: for both polarities of A2 referenced to A1.

Description

Fig. 1: Maximum power dissipation versus RMS on-state current (full cycle).




Fig. 2-1: RMS on-state current versus case temperature (full cycle).




Fig. 2-2: RMS on-state current versus ambient temperature (printed circuit board FR4, copper thickness: 35µm), full cycle.




Fig. 3: Relative variation of thermal impedance versus pulse duration.




Fig. 4: On-state characteristics (maximum values).





Fig. 5: Surge peak on-state current versus number of cycles.



Description

Fig. 6: Non-repetitive surge peak on-state current for a sinusoidal pulse with width $t_p < 10\text{ms}$, and corresponding value of I^2t .




Fig. 7: Relative variation of gate trigger current, holding current and latching current versus junction temperature (typical values).




Fig. 8-1: Relative variation of critical rate of decrease of main current versus $(dV/dt)_c$ (typical values) (BW/CW/T1235).




Fig. 8-2: Relative variation of critical rate of decrease of main current versus $(dV/dt)_c$ (typical values) (TW).




Fig. 9: Relative variation of critical rate of decrease of main current versus junction temperature.






Fig. 10: D²PAK Thermal resistance junction to ambient versus copper surface under tab (printed circuit board FR4, copper thickness: 35 µm).



Package Mechanical Data

TO-220AB (Plastic)



REF.	DIMENSIONS					
	Millimeters			Inches		
	Min.	Typ.	Max.	Min.	Typ.	Max.
A	15.20		15.90	0.598		0.625
a1		3.75			0.147	
a2	13.00		14.00	0.511		0.551
B	10.00		10.40	0.393		0.409
b1	0.61		0.88	0.024		0.034
b2	1.23		1.32	0.048		0.051
C	4.40		4.60	0.173		0.181
c1	0.49		0.70	0.019		0.027
c2	2.40		2.72	0.094		0.107
e	2.40		2.70	0.094		0.106
F	6.20		6.60	0.244		0.259
I	3.75		3.85	0.147		0.151
I4	15.80	16.40	16.80	0.622	0.646	0.661
L	2.65		2.95	0.104		0.116
I2	1.14		1.70	0.044		0.066
I3	1.14		1.70	0.044		0.066
M		2.60			0.102	