



FAST RECOVER RECTIFIER

BY296 THRU BY299

**VOLTAGE RANGE
CURRENT**


**100 to 800 Volts
2.0Ampere**

FEATURES

- Low coat construction
- Fast switching for high efficiency.
- Low reverse leakage
- High forward surge current capability
- High temperature soldering guaranteed:
260°C/10 secods/.375”(9.5mm)lead length at 5 lbs(2.3kg) tension

MECHANICAL DATA

- Case: Transfer molded plastic
- Epoxy: UL94V-O rate flame retardant
- Polarity: Color band denotes cathode end
- Lead: Plated axial lead, solderable per MIL-STD-202E method 208C
- Mounting position: Any
- Weight: 0.014 ounce, 0.39 grams



Dimensions in inches and (millimeters)

MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

- Ratings at 25°C ambient temperature unless otherwise specified
- Single Phase, half wave, 60Hz, resistive or inductive load
- For capacitive load derate current by 20%

	SYMBOLS	BY296	BY297	BY298	BY299	UNITS
Maximum Repetitive Peak Reverse Voltage	V_{RRM}	100	200	400	800	Volts
Maximum RMS Voltage	V_{RMS}	70	140	280	560	Volts
Maximum DC Blocking Voltage	V_{DC}	100	200	400	800	Volts
Maximum Average Forward Rectified Current 0.375”(9.5mm) lead length at $T_A=75^\circ\text{C}$	$I_{(AV)}$	2.0				Amp
Peak Forward Surge Current 8.3ms single half sine wave superimposed on rated load (JEDEC method)	I_{FSM}	70				Amps
Maximum Instantaneous Forward Voltage @ 2.0A	V_F	1.3				Volts
Maximum DC Reverse Current at Rated DC Blocking Voltage	$T_A=25^\circ\text{C}$	5.0				μA
	$T_A=100^\circ\text{C}$	200				
Maximum Reverse Recovery Time (Note 3) $T_J=25^\circ\text{C}$	t_{rr}	500				ns
Typical Junction Capacitance (Note 1)	C_J	25				pF
Typical Thermal Resistance (Note 2)	$R_{\theta JA}$	40				$^\circ\text{C}/\text{W}$
Operating Junction Temperature Range	T_J	(-55 to +150)				$^\circ\text{C}$
Storage Temperature Range	T_{STG}	(-55 to +150)				$^\circ\text{C}$

Notes:

1. Measured at 1.0MHz and Applied Reverse Voltage of 4.0Volts.
2. Thermal Resistance from junction to Ambient at .375”(9.5mm)lead length, P.C.board mounted.
3. Reverse Recovery Test Conditions: $I_f=10\text{mA}$, $I_r=10\text{mA}$, $I_{rr}=1\text{A}$



FAST RECOVER RECTIFIER

BY296 THRU BY299

VOLTAGE RANGE
CURRENT

100 to 800 Volts
2.0 Ampere

RATING AND CHARACTERISTIC CURVES BY296 THRU BY299

