

**Remark**


Material: Qualified NYLON66(Natural).

Usage: To fix PCB and board with good insulation, anti-rust anti-corrosion and light weight

Flame Class: 94V-2

Working Temperature: -20 °C ~ 120 °C

型号 PART NO	尺寸Dimension					包装 PACKAGE
	$\phi A$	$\phi B$	$\phi C$	D	E	
PTO-220	6.0	3.5	3.0	1.5	1.2	1000PCS
PTO-220A	6.0	3.5	3.0	2.0	1.2	
PTO-220B	6.0	3.5	3.0	2.5	1.5	
PTO-220D	6.0	3.5	3.0	3.0	1.5	
PTO-3 ✓	8.0	3.8	3.0	2.4	2.0	
PTO-5	10.0	5.0	3.8	3.0	1.5	



Material:

Drawing : 吴爱琴

Date: Nov. 22. 2012

Special:

Verify:

Date:

**CYX** 深圳市亚洲龙电子科技有限公司

SHEN ZHEN YAZHOULONG ELECTRONIC TECHNOLOGICAL CO.,LTD

Product Name: PTO Insulation Grain

Edition: A

Product Spec : PTO-3

Drawing Item :

Product Item :

Route:

未注公差参照  
 >0~10 ±0.2 >80~250 ±0.5  
 >10~30 ±0.3 >250~500 ±1.5  
 >30~80 ±0.4 >0~90° ±1°

单位: MM

Proportion:  
1:1

Approval:

Date: