

GLASS PASSIVATED BRIDGE RECTIFIERS

REVERSE VOLTAGE - 400to 1000 Volts
FORWARD CURRENT - 15 Amperes


FEATURES

- Rating to 1000V PRV
- Ideal for printed circuit board
- Reliable low cost construction utilizing molded plastic technique
- The plastic material has UL flammability classification 94V-0
- UL Recognition File # E95060

MECHANICAL DATA

- Polarity : As marked on Body
- Weight : 0.15 ounces, 4.0 grams
- Mounting position : Any

GBU



GBU		
DIM.	MIN.	MAX.
A	21.80	22.30
B	18.30	18.80
C	3.30	3.56
D	17.50	18.00
E	0.76	1.00
F	0.46	0.56
G	7.40	7.90
H	3.50	4.10
I	1.65	2.16
J	2.25	2.75
K	1.95	2.35
L	1.02	1.27
M	4.83	5.33
N	7.0° TYPICAL	
O	3.2 x 45°	
P	1.90 RADIUS	

All Dimensions in millimeter

MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Ratings at 25°C ambient temperature unless otherwise specified.
Single phase, half wave, 60Hz, resistive or inductive load.
For capacitive load, derate current by 20%

CHARACTERISTICS	SYMBOL	GBU 1504	GBU 1506	GBU 1508	GBU 1510	UNIT
Maximum Recurrent Peak Reverse Voltage	VRRM	400	600	800	1000	V
Maximum RMS Voltage	VRMS	280	420	560	700	V
Maximum DC Blocking Voltage	VDC	400	600	800	1000	V
Maximum Average Forward (with heatsink Note 2) Rectified Current @Tc=100°C (without heatsink)	I(AV)	15 3.2				A
Peak Forward Surge Current 8.3ms single half sine-wave superimposed on rated load	IFSM	200				A
Maximum forward Voltage at 7.5A DC	VF	1.1				V
Maximum DC Reverse Current @Tj =25°C at Rated DC Blocking Voltage @Tj =125°C	IR	5.0 500				uA
I ² t Rating for fusing (t < 8.3ms)	I ² t	166				A ² S
Typical Junction Capacitance per element (Note 1)	CJ	50				pF
Typical Thermal Resistance (Note 2)	RθJC	2.0				°C/W
Operating Temperature Range	TJ	-55 to +150				°C
Storage Temperature Range	TSTG	-55 to +150				°C

NOTES : 1.Measured at 1.0MHz and applied reverse voltage of 4.0V DC.
2.Device mounted on 200mm x 200mm x 5mm Al Plate Heatsink.

FIG.1 - FORWARD CURRENT DERATING CURVE




FIG.2 - MAXIMUM NON-REPETITIVE SURGE CURRENT




FIG.3 - TYPICAL REVERSE CHARACTERISTICS




FIG.4 - TYPICAL FORWARD CHARACTERISTICS




FIG.5 - TYPICAL JUNCTION CAPACITANCE

