



HIGH EFFICIENCY GLASS PASSIVATED RECTIFIER

HER601G THRU HER607G


VOLTAGE RANGE 50 to 1000 Volts
CURRENT 6.0 Ampere

FEATURES

- Glass passivated chip junction
- Low power loss, high efficiency
- Low leakage
- High speed switching
- High surge capacity
- High temperature soldering guaranteed
260°C/10 seconds, 0.375" (9.5mm) lead length

MECHANICAL DATA

- Case: Transfer molded plastic
- Epoxy: UL94V-0 rate flame retardant
- Polarity: Color band denotes cathode end
- Lead: Plated axial lead, solderable per MIL-STD-202E method 208C
- Mounting position: Any
- Weight: 0.07ounce, 2.0 gram



MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

- Ratings at 25°C ambient temperature unless otherwise specified
- Single Phase, half wave, 60Hz, resistive or inductive load
- For capacitive load derate current by 20%

	SYMBOLS	HER 601G	HER 602G	HER 603G	HER 604G	HER 605G	HER 606G	HER 607G	UNIT	
Maximum Repetitive Peak Reverse Voltage	V_{RRM}	50	100	200	300	400	600	800	Volts	
Maximum RMS Voltage	V_{RMS}	35	70	140	210	280	420	560	Volts	
Maximum DC Blocking Voltage	V_{DC}	50	100	200	300	400	600	800	Volts	
Maximum Average Forward Rectified Current 0.375" (9.5mm) lead length at $T_A=50^\circ\text{C}$	$I_{(AV)}$	6.0							Amps	
Peak Forward Surge Current 8.3ms single half sine-wave superimposed on rated load (JEDEC method)	I_{FSM}	200					150		Amps	
Maximum Instantaneous Forward Voltage at 6.0A	V_F	1.0			1.3		1.5	1.7	Volts	
Maximum DC Reverse Current at rated DC Blocking Voltage at	I_R	$T_A = 25^\circ\text{C}$							μA	
		10								
Maximum Full Load Reverse Current, full cycle average 0.375" (9.5mm) lead length at $T_L=55^\circ\text{C}$	$I_{R(AV)}$	$T_A = 125^\circ\text{C}$							μA	
		500								
Maximum Reverse Recovery Time Test conditions $I_F=0.5\text{A}$, $I_R=1.0\text{A}$, $I_{RR}=0.25\text{A}$,	t_{rr}	70				100			nS	
Typical Junction Capacitance (NOTE 2)	C_J	40								pF
Typical Thermal Resistance (NOTE 1)	$R_{\theta JA}$	20								$^\circ\text{C}/\text{W}$
Operating Junction Temperature Range	T_J	(-55 to +150)							$^\circ\text{C}$	
Storage Temperature Range	T_{STG}	(-55 to +150)							$^\circ\text{C}$	

Notes:

1. Thermal Resistance from Junction to ambient with 0.375" (9.5mm) lead length, PCB mounted.
2. Measured at 1.0MHz and applied reverse voltage of 4.0V



HIGH EFFICIENCY GLASS PASSIVATED RECTIFIER

HER601G THRU HER607G

VOLTAGE RANGE 50 to 1000 Volts
CURRENT 6.0 Ampere

RATING AND CHARACTERISTIC CURVES HER601G THRU HER607G

FIG.1-TYPICAL FORWARD CURRENT DERATING CURVE




FIG.2-MAXIMUM NON-REPETITIVE PEAK FORWARD SURGE CURRENT




FIG.3-TYPICAL INSTANTANEOUS FORWARD CHARACTERISTICS




FIG.4-TYPICAL REVERSE CHARACTERISTICS




FIG.5-TYPICAL JUNCTION CAPACITANCE





FIG.6-TEST CIRCUIT DIAGRAM AND REVERSE RECOVERY TIME CHARACTERISTIC



NOTES : 1.Rise Time=7ns max. Input Impedance= 1 megohm. 22pF
 2.Rise time=10ns max. Source Impedance= 50 ohms

SET TIME BASE FOR 50/100ns/cm