

JQX-14FA



CLASSIFICATION		PCB RELAY
Appearance 外型		JQX-14FA
Outline Dimension(L×W×H) 外形尺寸(mm)		28.9×12.6×20.6
Contact Form 触点形式		1A,1B,1C
Contact Resistance 接触电阻		100mΩ
Coil Voltage 线圈电压		5VDC ~ 48VDC
Pick-up Voltage 动作电压		≤80%
Release Voltage 释放电压		≥10%
Coil Power(W) 线圈功率 (瓦)		0.54,0.72
Contact Rating 触点容量		16A 240VAC/30VDC
Insulation Resistance 绝缘电阻		1000MΩ
Dielectric Strength 介质耐压	Between Open Contact 断开触点间	1000VAC
	Between Coil and Contact 触点线圈间	5000VAC
Life 寿命	Electrical 电气	1×10 <sup>5</sup>
	Mechanical 机械	1×10 <sup>7</sup>
Temperature Range 使用温度		-40 ~ +70°C
Terminal Layout 脚位图		
Mounting Holes(mm) 安装尺寸		
Mounting Form 安装形式		PCB Terminal
Weight 重量		13g
Safety Approval 安全标准		UL
Cross-Reference 型号对照		SCHRACK:RT OEG:OMI NAIS:JW ZETTLER:AZ742/763 764