





## Major ratings and characteristics

Characteristics	Values	Units
$I_{F(AV)}$ Rectangular Waveform	5 × 2	A
$V_{RRM}$	100	V
$V_F@ 5 A, T_J=125^{\circ}C$	0.64	V , typ.
$T_J$ Operating Junction Temperature	-65 to +175	$^{\circ}C$

TO-220AB



ITO-220AB




## Features

- \* Ultra-Low Forward Voltage Drop
- \* Reliable High Temperature Operation
- \* Softest, fast switching capability
- \* 175 $^{\circ}C$  Operating Junction Temperature
- \* Lead Free Finish, RoHS Compliant

## Typical Applications

Device optimized for ultra-low forward voltage drop to maximize efficiency in Power Supply applications



## Mechanical

- \* Molded Plastic Low profile TO-220AB / ITO-220AB
- \* Device Weight : 0.07 ounces (1.96grams) - TO-220AB  
0.06 ounces (1.74grams) - ITO-220AB
- \* Mounting Torque : 10 in-lbs maximum.

## Maximum Ratings Characteristics ( $T_A = 25^{\circ}C$ unless otherwise specified )

Parameter	Symbol		Units
DC Blocking Voltage	$V_{RM}$		
Working Peak Reverse Voltage	$V_{RWM}$	100	Volts
Peak Repetitive Reverse Voltage	$V_{RRM}$		
Average Rectified Forward Current (Rated VR-20Khz Square Wave) - 50% duty cycle	$I_o$	10	Amps
Peak Forward Surge Current - 1/2 60hz	$I_{FSM}$	120	Amps
Peak Repetitive Reverse Surge Current (2uS-1Khz)	$I_{RRM}$	1	Amps
Typical Thermal Resistance (per leg)	$R\theta_{Jc}$		$^{\circ}C / W$
Package = TO-220AB		2	
ITO-220AB		4	
Isolation voltage (ITO-220 only)	$V_{AC}$	1500	V
Maximum Rate of Voltage Change ( at Rated $V_R$ )	dv/dt	10000	V/uS
Operating Junction Temperature	$T_J$	- 65 to +175	$^{\circ}C$
Storage Junction Temperature	$T_{STG}$	- 65 to +175	



## Electrical Characteristics - (per leg) ( T<sub>A</sub> = 25°C unless otherwise specified )

Parameter	Test Conditions	Symbol	Typ.	Max.	Units
Instantaneous Forward Voltage	IF = 5 A	V <sub>F</sub> *	T <sub>J</sub> = 25°C	0.82	Volts
			T <sub>J</sub> = 125°C	0.64	
Instantaneous Reverse Current	At V <sub>RM</sub>	IR	T <sub>J</sub> = 25°C	100	uA
			T <sub>J</sub> = 125°C	10	mA

\* Pulse width < 300 uS, Duty cycle < 2%

## Patings and Characteristics Curves ( T<sub>A</sub> = 25°C unless otherwise specified )




Figure 1: Current Derating, Case




Figure 2: Maximum Repetitive Surge Current




Figure 3: Typical Forward Voltage




Figure 4: Typical Reverse Current





Figure 5: Typical Junction Capacitance



## Package Outline Dimensions millimeters



## Ordering information

Part Number	Package	Delivery mode
PFR10100CT	TO-220AB	50 pieces / tube
PFR10100CTF	ITO-220AB	50 pieces / tube

Note: For Halogen Free molding compound, add "H" suffix to part number above.

## Marking information

PFC  
PFR10100CT  
YYWW ABH

PFR10100CT = Product Type Marking Code  
YYWW = Date Code  
YY = Last two digits of year  
WW = Week code  
AB = Assembly code  
H = Halogen Free (N/A = common molding compound)

PFC Device Corp reserves the right to make changes without further notice to any products herein. PFC Device Corp makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does PFC Device Corp assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. "Typical" parameters which may be provided in PFC Device Corp data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. PFC Device Corp does not convey any license under its patent rights nor the rights of others. PFC Device Corp products are not designed, intended, or authorized for use as components in systems intended for surgical implant into the body, or other applications intended to support or sustain life, or for any other application in which the failure of the PFC Device Corp product could create a situation where personal injury or death may occur. Should Buyer purchase or use PFC Device Corp products for any such unintended or unauthorized application, Buyer shall indemnify and hold PFC Device Corp and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that PFC Device Corp was negligent regarding the design or manufacture of the part..